



Kayflo Filter Element, designed and constructed with specially formulated, resin impregnated medias utilizing synthetic fibers for maximum filtration and extended element life.

Ordering Information:

Product Number: KF6018-5, Size: 1 1/2", 3/4"

KF6018-5 Specifications

Outside Diameter	6.06"
Inside Diameter	2.63"
Length	18.0"
Weight	4.4 lbs.
Mean Efficiency	5
Absolute Efficiency	14
Dirt Holding Capacity	200 (Apparent Dirt Capacity Grams AC Fine Test Dust @ 25 PSID)
Water Removal	N/A
Minimum Collapse Pressure	75 PSID
Maximum Operating Temperature	250 Degrees Fahrenheit
Replacement Pressure PSID	25 PSID
Gasket Material	Nitrile
Flow Direction	Outside-In
Filter Type	Particulate
Flow Rate (per element)	47 GPM at 500 SSU (with 5 lb. Pressure Drop)

Applications

- Mineral base oil or fuel (diesel or jet)

Contact Green Marine & Industrial Equipment Co., Inc.

Toll Free (800) 483-5012

Louisiana office: 1111 Central Ave, Metairie, LA 70001 504-833-7386

Texas office: 340 Garden Oaks, Houston, TX 77018 713-242-9114